

WOOD SCREWS	64
CHIPBOARD SCREWS	64
REISSER CUTTER SCREW	65
DRYWALL SCREWS	65
FLOORING SCREWS	67
COACH SCREWS	67
DECKING SCREWS	67
SQUARE TWIST NAILS	67
OVAL BRAD NAILS	67
ROUND WIRE NAILS	68
ANNULAR RING SHANK NAILS	68
CLOUT NAILS	68
PLASTERBOARD NAILS	69
MASONRY NAILS	69
STAPLES	69
PINS	69
ROOFING & CLADDING FIXINGS	70
SECURITY SCREWS	71

SECTION 04

SCREWS & NAILS

Whether you need fixings for roofing, cladding or security, we have a massive selection of screws and nails to choose from. Call us if you can't find what you need.



SCREWS

TwinThread Wood Screw

Hardened steel, countersunk head, pozi, BZP.

SIZE (")	BOX QTY	SIZE (")	BOX QTY
4g x 1/2"	200	8g x 2.1/2"	100
6g x 1/2"	200	8g x 2.3/4"	100
6g x 5/8"	200	8g x 3"	100
6g x 3/4"	200	8g x 3.1/2"	100
6g x 1"	200	10g x 1"	200
6g x 1.1/4"	200	10g x 1.1/4"	200
6g x 1.1/2"	200	10g x 1.1/2"	200
6g x 1.3/4"	200	10g x 1.3/4"	200
6g x 2"	200	10g x 2"	200
7g x 3/4"	200	10g x 2.1/4"	100
7g x 1"	200	10g x 2.1/2"	100
7g x 1.1/4"	200	10g x 3"	100
8g x 1/2"	200	10g x 3.1/2"	100
8g x 3/4"	200	10g x 4"	100
8g x 1"	200	12g x 1"	200
8g x 1.1/4"	200	12g x 1.1/2"	200
8g x 1.1/2"	200	12g x 2"	100
8g x 1.3/4"	200	12g x 2.1/2"	100
8g x 2"	200	12g x 3"	100
8g x 2.1/4"	200	12g x 3.1/2"	100
		12g x 4"	100



Single Thread Chipboard Screw

Hardened steel, countersunk head, pozi, zinc & yellow passivated.

SIZE (MM)	BOX QTY	SIZE (MM)	BOX QTY	SIZE (MM)	BOX QTY
3.0 x 12	200	4.0 x 16	200	5.0 x 60	100
3.0 x 15	200	4.0 x 20	200	5.0 x 70	100
3.0 x 17	200	4.0 x 25	200	5.0 x 80	100
3.0 x 20	200	4.0 x 30	200	5.0 x 90	100
3.0 x 25	200	4.0 x 35	200	5.0 x 100	100
3.0 x 35	200	4.0 x 40	200	5.0 x 120	100
3.5 x 12	200	4.0 x 45	200	6.0 x 40	100
3.5 x 15	200	4.0 x 50	200	6.0 x 50	100
3.5 x 16	200	4.0 x 60	200	6.0 x 60	100
3.5 x 20	200	4.0 x 70	200	6.0 x 70	100
3.5 x 25	200	4.5 x 25	200	6.0 x 80	100
3.5 x 30	200	4.5 x 30	200	6.0 x 100	100
3.5 x 35	200	4.5 x 35	200	6.0 x 120	100
3.5 x 40	200	5.0 x 50	100	6.0 x 130	100
3.5 x 45	200	5.0 x 55	100	6.0 x 150	100
3.5 x 50	200				



Cordless drill drivers are available in the Power Tools section.



Reisser R2 Cutter Screw

Single thread, lubricated wood screw with slots to avoid splitting. Self-countersinks and does not require a pilot hole. Each batch is independently tested to guarantee consistency of quality. Yellow tropicalised for 20 times more rust resistance than BZP.

Well-defined ribs & tucks ensure self-countersinking in all timber & board materials.

Reinforced collar prevents snapping.

Lubricated, deep, sharp, wide thread allows fast, easy driving without a pilot hole.

Slots prevent splitting close to the edge.

Needle point for immediate start.

SIZE (MM)	BOX QTY	SIZE (MM)	BOX QTY
3.5 x 16	1000	4.5 x 30	1000
3.5 x 20	1000	4.5 x 40	500
3.5 x 25	1000	4.5 x 50	500
3.5 x 30	1000	4.5 x 60	500
3.5 x 40	1000	4.5 x 70	500
3.5 x 50	500	4.5 x 80	500
4.0 x 20	1000	5.0 x 40	500
4.0 x 25	1000	5.0 x 50	500
4.0 x 30	1000	5.0 x 60	500
4.0 x 35	1000	5.0 x 70	400
4.0 x 40	500	5.0 x 80	400
4.0 x 45	500	5.0 x 100	400
4.0 x 50	500	6.0 x 50	400
4.0 x 60	500	6.0 x 60	200
4.0 x 70	500	6.0 x 80	200
		6.0 x 100	200

Hardened Steel Drywall Screw

Fine thread, bugle head, phillips, BZP & black phosphate.

SIZE (MM)	BOX QTY	SIZE (MM)	BOX QTY
3.5 x 25	1,000	3.5 x 50	1,000
3.5 x 32	1,000	3.5 x 55	500
3.5 x 35	1,000	3.5 x 60	500
3.5 x 38	1,000	4.2 x 65	500
3.5 x 42	1,000	4.2 x 75	500
		4.8 x 100	200

Each small box contains 1 screwdriver bit, packed in a small plastic bag.

Hardened Steel Drywall Screw

Coarse thread, bugle head, phillips, black phosphate.

SIZE (MM)	BOX QTY
3.5 x 25	1,000
3.5 x 32	1,000
3.5 x 38	1,000
3.5 x 42	1,000
4.2 x 65	500
4.2 x 75	500

Each small box contains 1 screwdriver bit, packed in a small plastic bag.



Self Drilling Drywall Screw

Hardened steel, fine thread, bugle head, phillips, BZP.

SIZE (MM)	BOX QTY
3.5 x 25	1,000
3.5 x 32	1,000
3.5 x 35	1,000
3.5 x 38	1,000
3.5 x 42	1,000
3.5 x 45	1,000
3.5 x 50	1,000
3.5 x 55	500
3.5 x 60	500
4.2 x 65	500
4.2 x 75	500
4.8 x 100	200

Each small box contains 1 screwdriver bit, packed in a small plastic bag.



Drywall Wafer & Pan Head Screw

SIZE (MM)	DESCRIPTION	BOX QTY
4.2 x 13	Wafer Head Needle Point & Self Drilling	1,000
4.2 x 13	Pan Head Self Drilling	1,000
4.2 x 25	Wafer Head Self Drilling	1,000

Collated Drywall Screw

Fine & coarse thread, bugle head, phillips, BZP & black phosphate.

SIZE (MM)	BOX QTY
3.5 x 25	1,000
3.5 x 32	1,000
3.5 x 35	1,000
3.5 x 38	1,000
3.5 x 42	1,000
3.5 x 45	1,000
3.5 x 50	1,000

Collated Screwdrivers available, see pages 12, 14 of the Power Tools and Accessories section.



Duraspin Collated Drywall Screw

Fine & coarse thread, bugle head, phillips, black phosphate.

SIZE (MM)	COARSE THREAD	FINE THREAD	FERMACEL	FINE THREAD DRILL-TIP	BOX QTY
3.9 x 25	•				1,000
3.9 x 35	•				1,000
3.9 x 45	•				1,000
3.9 x 50	•				1,000
3.9 x 55	•				1,000
4.5 x 75	•				1,000
3.9 x 30			•		1,000
3.9 x 45			•		1,000
3.9 x 25		•			1,000
3.9 x 35		•			1,000
3.9 x 45		•			1,000
3.5 x 25				•	1,000
3.5 x 35				•	1,000
3.5 x 45				•	1,000



Plasterboard tapes available, see page 78 of the Adhesives section.

Flooring Screw

Yellow passivated. Collated also available.

SIZE (MM)	BOX QTY
4.2 x 45	1,000
4.2 x 55	1,000
4.2 x 63	1,000
4.2 x 75	1,000



Coach Screws

Hex head, BZP.

SIZE (MM)	M6	M8	M10	M12
30	•			
40	•	•	•	
45		•		
50	•	•	•	
60	•	•	•	
65		•	•	
70	•	•	•	
75	•	•	•	
80	•	•	•	•
90	•	•	•	
100	•	•	•	•
120		•	•	•
140			•	
150		•	•	•
160			•	
180			•	
200			•	•



Decking Screws

SIZE (MM)	DRIVE	BOX QTY
4.2 x 40	Square	200
4.2 x 50	Square	200
4.2 x 63	Square	200
4.2 x 75	Square	200
4.2 x 90	Square	200

Decking Screw (A2 Stainless)

SIZE (MM)	DRIVE	BOX QTY
4.2 x 50	Square	200
4.2 x 63	Square	200




NAILS

Square Twist Nails

Galvanised, sheradised.


SIZE (MM)
30, 40



Oval Brad Nails

Bright, galvanised lost head. Reduces spitting in hard or brittle timber. Ideal nails for general joinery & aligning with grain.

SIZE (MM)
25, 30, 40, 50, 60, 65, 75, 100, 125, 150



Round Wire Nails

Bright or galvanised. Ideal for the professional and domestic user alike.

LENGTH (MM)	GAUGE (MM)
20	1.60
25	1.60
25	1.80
25	2.00
30	2.65
40	2.36
40	2.65
45	2.00
45	2.36
50	2.36
50	2.65
50	3.00
50	3.35
60	2.65
60	3.35



LENGTH (MM)	GAUGE (MM)
65	2.65
65	3.35
75	3.00
75	3.35
75	3.75
75	4.00
90	4.00
100	3.75
100	4.00
100	4.50
100	5.00
125	5.00
125	5.60
150	6.0



Number of Round Wire Nails per kg. (approx.)

LENGTH (MM)	20	25	30	40	45	50	60	65	75	90	100	115	125	150
Gauge (mm)														
1.6		2685	2295											
1.8		1847												
2.0		1446	1241	891	882									
2.36				661	591	538								
2.65				542		441	372	346						
3.0						342		265						
3.35						284	236	216	187					
3.75									145					
4.0									128	106	101			
4.5											79			
5.0											66	55	51	
5.6													42	
6.0														31



Annular Ring Shank Nails

Bright, sheradised and stainless steel. Used where permanent strength and holding power are of primary importance.

LENGTH (MM)	GAUGE (MM)
20	2.00
25	2.00
30	2.36
30	2.50
40	2.50
40	2.65
45	2.65
50	2.50
50	2.65
50	3.35
60	3.35
65	3.35
75	3.75
100	5.00
125	5.00



Galvanised, Aluminium and Copper Clout Nails

LENGTH (MM)	GAUGE (MM)
20	2.65
25	2.65
30	2.36
30	2.65
30	3.00
40	2.65
40	3.35
50	2.65
50	3.35
65	3.35
65	3.75
75	3.35
75	3.75



E.L.H. Galvanised Clout Nails

For fixing of non-rigid roll roofings, smooth or grit surface.

LENGTH (MM)	GAUGE (MM)
13	3.00
20	3.00
25	3.00
30	3.00
40	3.00
50	3.00



Jagged Plasterboard Nails

Indented shank and countersunk head, these nails are ideal for plasterboard fixings and cladding.

LENGTH (MM)	GAUGE (MM)
30	2.65
40	2.65



All nails come supplied in 25kg boxes, 1kg, 2.5kg, 5kg, 10kg, 20kg available upon request.

Masonry Nails

SIZE (MM)	LIGHT GAUGE (2.5MM Ø)	MEDIUM GAUGE (3MM Ø)	HEAVY GAUGE (3.5MM Ø)	BOX QTY
22	•	•		100
25	•	•	•	100
30	•	•	•	100
35	•	•	•	100
40	•	•	•	100
45		•	•	100
50	•	•	•	100
55	•	•	•	100
60	•	•	•	100
65	•	•	•	100
70	•	•	•	100
75		•	•	100
80		•	•	100
85		•	•	100
90			•	100
100			•	100



Washed Masonry Nails (Mickey Pin)

SIZE (MM)	LIGHT GAUGE (2.5MM Ø)	BOX QTY
30	•	200

Galvanised Staples

With presser points.

SIZE (MM)	APPROX. NO. PER KG
20	1.60
25	1.60
25	1.80
25	2.00
30	2.00
40	2.36
40	2.65
45	2.00
45	2.36
50	2.36
50	2.65
50	3.00
50	3.35
60	2.65
60	3.35

Panel Pins

Bright. Ideal for lightweight and decorative jobs.

LENGTH (MM)	GAUGE (MM)
15	1.25
20	1.40
20	1.60
25	1.40
25	1.60
30	1.60
40	1.60
50	2.00

Veneer Pins

Bright. For use with wood veneers.

LENGTH (MM)	GAUGE (MM)
25	1.00
20	1.00
25	1.00



ROOFING & CLADDING FIXINGS

TEK SCREWS

Hex Head, light section

Coarse thread. Steel thickness 1.2 – 3.5mm, G16 / G19 washer available.

SIZE (MM)	BOX QTY
5.5 x 20	500
5.5 x 25	500
5.5 x 32	200
5.5 x 38	200
5.5 x 50	100
5.5 x 65	100
5.5 x 80	100
5.5 x 100	100



Hex Head, heavy section

Fine thread. Steel thickness 4 – 12.5mm, G16 / G19 washer available.

SIZE (MM)	BOX QTY
5.5 x 25	200
5.5 x 32	200
5.5 x 38	100
5.5 x 50	100
5.5 x 70	100
5.5 x 100	100



Metal Framing Applications

SIZE (MM)	DESCRIPTION	BOX QTY
4.8 x 16	Pancake Head	500
4.8 x 22	Wafer Head (Zinc Plated)	500
5.5 x 25	Pancake Head	200
5.5 x 38	Low Profile Head	200



TIMBER TEK SCREWS

Countersunk screw, light section

Coarse thread. Steel thickness 1.2 – 3.5mm

SIZE (MM)	BOX QTY
4.2 x 38	200
4.8 x 45	100
5.5 x 50	200
5.5 x 62	200
5.5 x 80	100
5.5 x 100	100
5.5 x 120	100



Countersunk Screw, heavy section

Fine thread. Steel thickness 4 – 12.5mm

SIZE (MM)	BOX QTY
5.5 x 42	100
5.5 x 65	100
5.5 x 85	100
5.5 x 100	100



Rivets

SIZE (MM)	MATERIAL
3.2 x 10	Aluminium
4.0 x 10	Aluminium
3.2 x 10	White Steel
4.0 x 10	White Steel




Tek Screws Accessories

SIZE (MM)	BOX QTY
G16 Bonded washer	500
G19 Bonded washer	500



Foil tape available on page 78 of the Adhesives section.



SECURITY SCREWS

All security screws are manufactured in A2 Stainless Steel, suitable for internal and external applications and are available in box quantities of 100 units.

2 Hole Security Screws

Screws have 2 small holes drilled into the head, therefore they can only be removed by using unique 2 pin driver.

- Countersunk & pan head self tappers AB type thread.
- Countersunk & pan head machine screws.
- Raised countersunk machine screws.

Tamper Resistant Pin Hex Socket Screws

Screws have an internal pin within the standard socket aperture, this prevents the use of standard socket keys. Screws are virtually impossible to remove without the matching screwdriver.

- Countersunk & button head self tappers AB type thread.
- Countersunk & button head machine screws.
- Raised countersunk machine screws.

6 Lobe / Resistorx Security Screws

Screws have Star Drive with internal pin. Screws are virtually impossible to remove without the matching screwdriver.

- Countersunk & button head self tappers AB type thread.
- Countersunk & button head machine screws.
- Raised countersunk machine screws.

Clutch Head / Sentinel® Screws

Screws only operate in clockwise motion, ideal permanent fixing and installed with standard slotted screwdriver.

- Countersunk & button head self tappers AB type thread.

Security Grille Anchors (Drill Out)

8.8 grade yellow passivated steel which will fix material up to 30mm to masonry. Simply fix anchor then drill out socket removing hexagon flats. Leaves permanent secure fixing.

Security Grille Anchor (Hex Socket Pin)

10.9 grade yellow passivated steel which will fix material up to 30mm to masonry. Useful option where anchor needs to be removed. Installed or removed with HSP insert bit.

Armour Rings™

Available in plated steel or stainless steel. Simple conical collar makes standard bolts and nuts tamperproof.

Security Tools

Standard Magnetic Hand Drivers: 1/4" Hex Drive

Ratchet Magnetic Hand Drivers: 1/4" Hex Drive

2 Hole 1/4" Hex Insert Bits: TH3, 4, 5, 6, 7, 8

Hex Socket Pin 1/4" Hex Insert Bits: H20, 30, 40, 50, 60, 80

Hex Socket Pin 1/4" Key Wrench: H20, 30, 40, 50, 60, 80

6 Lobe Pin 1/4" Hex Insert Bits: T15, 20, 25, 27, 30, 40, 45

6 Lobe Pin 1/4" Key Wrench: T15, 20, 25, 27, 30, 40, 45

1/4" Socket Set Adaptor

3/8" - 1/4" Drive Adaptor

1/2" - 3/8" Drive Adaptor

Clutch Head Removal Tool: RT41 6+8g, RT51 8+10g, RT61 12+14g

Security Grille Anchor 1/4" Hex Insert Bits: 5mm, 6mm, 5mm HSP, 6mm HSP

